

WHAT YOU'LL NEED

- Philips head screwdriver (included) (Size: PH2)
- Socket wrench (included) (Size: 10mm)
NOTE: If you own similar tools that you are more comfortable with, feel free to use them. However, when installing the UI/Control Panel, we recommend using the included screwdriver due to space constraints. DO NOT USE POWER TOOLS.
- An extension cord (look on the labels for cords rated for outdoor use)
- An assembly partner to help you lift the firebox since it's a 2-person job
- Propane tank for testing/first ignition

THINGS TO KEEP IN MIND

- Check for and remove items from inside the firebox before lifting.
- Some parts come pre-installed (ex: temperature control dial).
- Plastic bags are labeled but the parts are not—take your time and follow the assembly guide step by step to avoid misplacing parts.
- Assemble grill on a flat, level, non-abrasive surface.
- Always keep lid closed when assembling or moving your grill.
- When assembling the UI/control panel, take note of all the connectors to make sure they are seated properly and fully connected.
- If any parts are missing or if you lose one, locate your hardware pack as extra hardware is included for these scenarios. If you need further assistance, please contact SharkNinja for assistance at support.ninjakitchen.com.

ASSEMBLY RESOURCES

- [FlexFlame Assembly Guide](#) (included in box, digital copy available on support.ninjakitchen.com).
- Download the [BILT app](#) for easy 3D interactive assembly instructions.
- Watch our [assembly video](#) with The Grill Dads on YouTube.

QUICK TIPS FOR A SMOOTH ASSEMBLY

- Use the box as a protective assembly area to prevent scratches.
- Once you've assembled the wheels for the base, make sure to lock them to prevent them from moving until you are ready to move the grill to its destination.
- Wait to cut the zip-tie on the regulator hose until Step #11 in the assembly guide.
- When installing control panel, make sure the clip is inserted properly to prevent gaps. Remember to remove the sticker on the shelf first.
- If you have difficulty installing the tank divider, loosen the screws of the back panel to install the divider before tightening the screws again.
- Locate and place hands on the LIFT HERE stickers (located at each corner of the firebox) to stay safe while lifting.

To make the firebox easier to lift, we recommend removing the firebox lid. To do this, remove the cotter pins (they resemble hairpins) on each side of the lid hinges and slide the lid off to the left. Once the firebox is in place, you may re-attach the lid using the hairpins.

DOUBLE CHECK EVERYTHING IS ASSEMBLED

- ☐ Ensure all parts and screws are secure before operating or moving the grill.
- ☐ Make sure to check all electronic connectors are properly secure and seated.
 - ☐ Under the right side table after removing the connector cover.
 - ☐ Under the control panel on one of the insulation sleeves.
- ☐ Before testing/first use, make sure your propane tank is securely in the cabinet and the regulator hose is fully attached.